

LSL SERIES striplight

garages
stairwells
offices
corridors
healthcare







FEATURES

- 48" x 4-7/8" channel with multiple 1/2" knockouts on all sides to allow for numerous power input options
- Surface mount to a ceiling or wall
- End-to-end mounting
- 120-277V power input
- 34W, 4100 Source Lumens
- Adjustable CCT 3000K or 4000K
- 90 CRI


- 50,000 hour rated, 5-year warranty
- EM Battery Back-up option (BB)
 - 90 minute run time
 - 9.5VDC LiFePO4 battery
 - 8 Watts
- Bi-Level Motion Sensor option (MS)
 - Built-in daylight sensor
 - Detection area, time delay, dimming level, and daylight threshold can be precisely set via DIP switch
 - Wide detection area, range up to 50 ft. max

MOTION SENSOR SPECS


TRANSMITTING POWER	<1mW
POWER CONSUMPTION	≤0.5W(standby), <1W(operation)
DETECTION ZONE	Max.(DxH): 16m x 15m
DETECTION SENSITIVITY	10% / 50% / 75% / 100%
HOLD TIME	5s / 30s / 90s / 3 min/ 20 min / +∞
DAYLIGHT SENSOR	2lux / 5lux / 10lux / 25lux / 50lux / 100lux/ Disable
STAND-BY PERIOD	0s / 5s/ 5 min/ 10 min / 30 min / 1h / +Disable
STAND-BY DIMMING LEVEL	10% / 20% / 30% / 50%
MOUNTING HEIGHT	15m Max.
MOTION DETECTION	0.5-3m/s
DETECTION ANGLE	150° (wall installation), 360° (ceiling installation)




With sufficient light, the fixtures will not switch on.



With insufficient light, the fixtures turn on at desired dimming level (10% - 50%).



When motion is detected, fixtures switch to full light output.



After standby period of no motion, fixtures return to desired dimming level (10%-50%).

LSL SERIES striplight

garages
stairwells
offices
corridors
healthcare



Construction

Housing is die-formed of 22-gauge steel. Standard mounting holes are included. Power supply connections can be made inside the fixture wire way or in a junction box (not included).

Finish

Housing is finished in lighting grade white baked gloss enamel paint.

Diffuser


White acrylic diffuser.

Certification

cETLus listed for indoor damp locations.
ENERGY STAR® qualified.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.



Ordering Information

Non-Dimming

	LED	Source Lumens	Delivered Lumens	Adjustable CCT	L	W	D
LSL484100LAJMVWH	34W	4100	3500	3000K or 4000K	48"	4-7/8"	3-1/2"
LSL484100LAJMVWHBB Emergency Battery Back-Up	34W	4100	3500	3000K or 4000K	48"	4-7/8"	3-1/2"

With Dimming Motion Sensor

	LED	Source Lumens	Delivered Lumens	Adjustable CCT	L	W	D
LSL484100LAJD2WH-MS Motion Sensor	34W	4100	3100	3000K or 4000K	48"	4-7/8"	3-1/2"
LSL484100LAJD2WH-MSBB Emergency Battery Back-Up W/ Motion Sensor	34W	4100	3100	3000K or 4000K	48"	4-7/8"	3-1/2"



2345 N. Ernie Krueger Circle
Waukegan, IL 60087
AFXinc.com